

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-045582
 (43)Date of publication of application : 15.02.1990

(51)Int.Cl. C09J 7/02
 B32B 5/16
 C09J 7/02

(21)Application number :	63-195682	(71)Applicant :	NITTO DENKO CORP
(22)Date of filing :	05.08.1988	(72)Inventor :	SUNAKAWA MAKOTO MATSUMOTO TOSHIHIKO

(54) AIR PERMEABLE TACKY MEMBER AND PRODUCTION THEREOF

(57)Abstract:

PURPOSE: To obtain a tacky member having excellent adhesion, air permeable properties and maintenance of vent hole by providing an air permeable tacky layer containing hollow beads on a porous air permeable substrate and providing a number of fine pores communicating with pores in the above-mentioned substrate in the tacky layer.

CONSTITUTION: A tacky liquid blending with hollow beads 11 having 10-100 μ m average particle is applied to an air permeable substrate 2 having a number of pores 21 having 1-50 μ m average pore size. The formed coating layer is treated through pores 21 in an air permeable substrate 2 by a gas blow system or air suction system to partially remove the tacky liquid and form a number of fine pores 12. Then the coating layer having the fine pores 12 is subjected to drying treatment to form the air permeable tacky layer 1.

